

fibre as a reinforcement in the green composite may result in much economical and eco-friendly solution for automotive and other industries.

REFERENCES

- [1] Cho, J., Chen, J.Y., Daniel, I.M. (2007). Mechanical enhancement of carbon fiber/epoxy composites by graphite nano platelet reinforcement. *Scripta Materialia*, 56(8): 685-688. <https://doi.org/10.1016/j.scriptamat.2006.12.038>
- [2] Shinichi, S., Yong, C., Isao, F. (2005). Press forming of short natural-fiber reinforced biodegradable resin: Effects of fiber volume and length on flexural properties. *Polymer Testing*, 24(8): 1005-1011. <https://doi.org/10.1016/j.polymertesting.2005.07.012>
- [3] Mateusz, S., Marek, M., Maciej, B., Ewa, G. (2015). Mechanical properties of sawdust and woodchips. *Fuel*, 159: 900-908. <https://doi.org/10.1016/j.fuel.2015.07.044>
- [4] Sombatsompand, N., Chaochanchaikul, K. (2004). Effect of moisture content on mechanical properties, thermal and structural stability and extrudate texture of poly (vinyl chloride)/wood sawdust composites. *Polymer International*, 53(9): 1210-1218. <https://doi.org/10.1002/pi.1535>
- [5] Maries, I., Abderrahim, B., Umadevi, L., Laurent, I.L., Sabu, T. (2006). Thermophysical properties of natural fiber reinforced polyester composites. *Compos Sci Technol*, 66(15): 2719-2725. <https://doi.org/10.1016/j.compscitech.2006.03.007>
- [6] Guohua, W., Bharat, B., Peter, M.T. (2005). Nanochemical characterization of human hair using nanoindentation and SEM. *Ultramicroscopy*, 105(1-4): 248-66. <https://doi.org/10.1016/j.ultramic.2005.06.033>
- [7] Geethamma, V.G., Kalaprasad, G., Gabriel, G., Sabu, T. (2005). Dynamic mechanical behavior of short coir fiber reinforced natural rubber composites. *Composites Part A: Applied Science and Manufacturing*, 36(11): 1499-506. <https://doi.org/10.1016/j.compositesa.2005.03.004>
- [8] Hammami, M., Mahi, A.E., Karra, C., Haddar, M. (2016). Nonlinear behaviour of glass fibre reinforced composites with delamination. *Composites Part B: Engineering*, 92: 350-359. <https://doi.org/10.1016/j.compositesb.2016.02.031>
- [9] Fakhrul, T., Islam, M.A. (2013). Degradation behaviour of natural fiber reinforced polymer matrix composites. *Procedia Engineering*, 56: 795-800. <https://doi.org/10.1016/j.proeng.2013.03.198>
- [10] Sombatsompop, N., Chaochanchaikul, K. (2004). Effect of moisture content on mechanical properties, thermal and structural stability and extrudate texture of poly (vinyl chloride)/wood sawdust composites. *Polymer International*, 53(9): 1210-1218. <https://doi.org/10.1002/pi.1535>
- [11] Arivukkarasan, S., Dhanalakshmi, V., Stalin, B., Ravichandran, M. (2018). Mechanical and tribological behaviour of tungsten carbide reinforced aluminum LM4 matrix composites. *Particulate Science and Technology*, 36(8): 967-973. <https://doi.org/10.1080/02726351.2017.1331285>