











## REFERENCES

- [1] Eschenauer L, Gligor VD. (2002). A key-management scheme for distributed sensor networks. in Proc. of 9th ACM Conf. Comput. Commun. Security, ACM, NewYork, USA: 41-47.
- [2] Chan H, Perrig A, Song D. (2003). Random key pre distribution schemes for sensor networks. In Proc. IEEE Symp. Research Security Privacy, MA. Kluwer, Norwell: 197-213.
- [3] Du W, Deng J, Han YS, and P. K. Varshney (2005). A pairwise key pre distribution scheme for wireless sensor networks. ACM Trans. Inf. Syst. Security 8(2): 228-258.
- [4] Lee J, Stinson DR. (2004). Deterministic key pre distribution schemes for distributed sensor networks. In Proc. 11th Workshop Sel. Areas Cryptography, Waterloo, Canada, 294-307. [https://doi.org/10.1007/978-3-540-30564-4\\_21](https://doi.org/10.1007/978-3-540-30564-4_21)
- [5] Lee J, Stinson DR. (2005). A combinatorial approach to key pre distribution for distributed sensor networks. in Proc. IEEE Wireless Commun. Netw. Conf., Mar., 13-17. <https://doi.org/10.1109/WCNC.2005.1424679>
- [6] Liu DG, Ning P. (2005). Establishing pairwise keys in distributed sensor networks. In ACM Trans. Inf. Syst. Security 8(1): 41-77. <https://doi.org/10.1145/948109.948119>
- [7] Zhu S, Xu S, Setia S, Jajodia S. (2003). Establishing pairwise keys for secure communication in ad hoc networks: a probabilistic approach. In Proc. 11th IEEE International Conf. Netw. Protocols, Atlanta, GA, 326-335. <https://doi.org/10.1109/ICNP.2003.1249782>
- [8] Landstra T, Zawodniok M, Jagannathan S. (2007). Energy-efficient hybrid key management protocol for wireless sensor networks. In IEEE Conf. Local Comput. Netw., Rolla, MO, 559-562. <https://doi.org/10.1109/LCN.2007.64>
- [9] Gaafar M, Khafagy MG, Amin O, Alouini MS. (2016). Improper Gaussian signaling in Full duplex relay channels with residual self-interference. Proc. IEEE Int. Conf. Commun. (ICC), Kuala Lumpur, May. <https://doi.org/10.1109/ICC.2016.7511009>
- [10] Sboui L, Ghazzai H, Rezki Z, Alouini MS. (2015). Achievable rate of a cognitive MIMO multiple access channel with multi-secondary users. IEEE Communications Letters 19(9): 403-406. <https://doi.org/10.1109/LCOMM.2014.2387843>
- [11] Wang L, Kim KJ, Duong TQ, Elkashlan M, Poor HV. (2015). Security enhancement of cooperative single carrier systems. IEEE Transactions on Wireless Communications 10(1): 90-103. <https://doi.org/10.1109/tifs.2014.2360437>
- [12] Yang WW, Zhao XH. (2017). Robust resource allocation for orthogonal frequency division multiplexing-based cooperative cognitive radio networks with imperfect CSI. IET Communications 11(2): 273-281. <https://doi.org/10.1049/iet-com.2016.0742>
- [13] Kim SJ, Soltani N, Giannakis G. (2013). Resource allocation for OFDMA cognitive radios under channel uncertainty. IEEE Transactions on Wireless Communications 12(7): 3578-3587. <https://doi.org/10.1109/TWC.2013.062413.121892>
- [14] Kailkhura B, Nadendla VSS, Varshney PK. (2015). Distributed inference in the presence of eavesdroppers: A survey. IEEE Communications Magazine 53(6): 40-46. <https://doi.org/10.1109/MCOM.2015.7120015>
- [15] Elkashlan M, Wang L, Duong TQ, Karagiannidis GK, Nallanathan A. (2015). On the security of cognitive radio networks. IEEE Transactions on Vehicular Technology 64(8): 3790-3795. <https://doi.org/10.1109/TVT.2014.2358624>
- [16] Cai Y, Mo Y, Ota K, Luo C, Dong M, Yang LT. (2014). Optimal data fusion of collaborative spectrum sensing under attack in cognitive radio networks. IEEE Network 28(1): 17-23. <https://doi.org/10.1109/MNET.2014.6724102>
- [17] Najimi M, Ebrahimzadeh A, Andargoli S, Fallahi A. (2013). A novel sensing nodes and decision node selection method for energy efficiency of cooperative spectrum sensing in cognitive sensor networks. IEEE Journal on Sensors 13(5): 1610-1621. <https://doi.org/10.1109/JSEN.2013.2240900>
- [18] Zou Y, Champagne B, Zhu WP, Hanzo L. (2015). Relay-selection improves the security reliability trade-off in cognitive radio systems. IEEE Transactions on Communications 63(1): 215-228. <https://doi.org/10.1109/tcomm.2014.2377239>
- [19] Deng X, Haimovich AM. (2005). Power allocation for cooperative relaying in wireless networks. IEEE Communication Letters 9(9): 994-996. <https://doi.org/10.1109/LCOMM.2005.11012>
- [20] Yang J, Ulukus S. (2012). Optimal packet scheduling in an energy harvesting communication system. IEEE Transactions on Communications 60(1): 220-230. <https://doi.org/10.1109/tcomm.2011.112811.100349>
- [21] Wu YQ, Hu F, Zhu YY, Kumar S. (2017). Optimal Spectrum handoff control for cognitive radio network based on hybrid priority queuing and multi teacher apprentice learning. IEEE Transactions on Vehicular Technology 66(3): 2630-2642.
- [22] Xu XM, Yang WW, Cai YM. (2017). Opportunistic relay selection improves reliability-reliability tradeoff and security-reliability tradeoff in random cognitive radio networks. IET Communications 11(3): 335-343. <https://doi.org/10.1049/iet-com.2016.0702>
- [23] Malathi P, Vanathi PT. (2008). OFDM for wireless local area network systems. AMSE Journals, Series Advances B51(1): 1-16, 26.
- [24] Perarasi T, Nagarajan G, Abinaya P. (2016). Controlled channel sharing for Cognitive Radio networks. Australian Journal of basic and applied Sciences 10(12): 82-90, 29.