

addition, a weak mixing process can lead to a stable thermocline, which reflect a stability in temperature curves.

REFERENCES

- [1] Koppen Van CWJ, Thomas JPX, Veltkamp WB. (1979). The actual benefits of thermally stratified storage in a small and medium size solar system. Proceedings of ISES Solar World Congress.
- [2] Bu-Hamdan MG, Zurigat YH, Ghajar AJ. (1989). Experimental study of a stratified thermal storage under variable inlet temperature for different inlet designs. Proceedings of 26th National Heat Transfer Conference AIChE Symposium Series 85: 269166-174.
- [3] Lin JY, Shyu RJ, Fang LJ. (1987). Study of thermal stratification in storage tank with charging. Journal of Chinese Society of Mechanical Engineering 8: 87-94.
- [4] Han YM, Wang RZ, Dai YJ. (2009). Thermal stratification within the water tank. Renewable and Sustainable Energy Reviews 13: 1014-1026
- [5] Zachàr A, Farkas I, Szlivka F. (2003). Numerical analyses of the impact of plates for thermal stratification inside a storage tank with upper and lower inlet flows. Solar Energy 74: 287-302
- [6] Altuntop N, Ozceyhan V, Tekin Y, Gunes S. (2008). The effect of obstacle geometry and position on thermal stratification in solar hot water storage tanks. ASME 2008 Heat Transfer Summer Conference collocated with the Fluids Engineering, Energy Sustainability, and 3rd Energy Nanotechnology Conferences pp. 479-484.
- [7] Bonanos A, Votyakov E. (2016). Sensitivity analysis for thermocline thermal storage tank design. Renew. Energy 99: 764-771.
- [8] Erdemir D, Altuntop N. (2016). Improved thermal stratification with obstacles placed inside the vertical mantled hot water tanks. Appl. Therm. Eng. 100: 20-29.
- [9] Eames PC, Norton B. (1996). An evaluation of the effect of storage tank geometry on store performance, using a transient 3-dimensional numerical model validated for a wide range of thermally stratified hot water stores, when subject to low Reynolds number flows. Proceedings of Eurotherm Seminar 49.
- [10] Yee CK, Lai FC. (1999). Effects of a porous manifold on thermal stratification in a liquid storage tank. Solar Energy 71: 241-254.
- [11] Cònsul R, Rodríguez I, Pérez-Segarra CD, Soria M. (2004). Virtual prototyping of storage tanks by means of three-dimensional CFD and heat transfer numerical simulations Solar Energy 77: 179-191.
- [12] Shah LJ, Furbo S. (2003). Entrance effects in solar storage tanks Solar Energy 75337-348.
- [13] Johannes K, Fraisse G. (2005). Comparison of solar water tank storage modeling solutions. Solar Energy 79216-218.
- [14] Levers S, Lin W. (2009). Numerical simulation of three-dimensional flow dynamics in a hot water storage tank. Applied Energy 86: 2604-2614.
- [15] Savicki DL, Vielmo HA, Krenzinger A. (2011). Three-dimensional analysis and investigation of the thermal and hydrodynamic behaviours of cylindrical storage tank. Renewable Energy 36 1364-1373.
- [16] Yang Z, Chen H, Wang L, Sheng Y, Wang Y. (2016). Comparative study of the influences of different water tank shapes on thermal energy storage capacity and thermal stratification. Renewable Energy 85: 31-44.
- [17] Density KGS. (1975). Thermal expansivity, and compressibility of liquid water from 0c° to 150c°: Correlations and tables for atmospheric pressure and saturation reviewed and expressed on 1968 749 temperature scale. Journal of Chemical & Engineering Data 20(1): 97-105
- [18] Kestin J, Whitelaw JH. (1966). 6th Int. Conf. on the properties of steam-transport properties of water substances. J. Engng. Pwr. 88(1).