

to additional cost of backfilling, the increased recovery of the resource and possible reduced dilution pays for this extra cost.

ACKNOWLEDGEMENTS

The researchers greatly appreciate the KCM management to accord permission to carry out this research and also the supporting staff for being helpful at the mine during the gathering of data.

REFERENCES

- [1] Donovan JG. (1999). The effects of backfilling on ground control and recovery in thin-seam coal mining, MSc Thesis, Blacksburg, Virginia Polytechnical Institute and State University, Virginia, 1-4.
- [2] Hartman HL. (1992). SME Mining Engineering Handbook. 2nd ed. Society for Mining, Metallurgy, and Exploration, Inc, Colorado, 1717-1728.
- [3] Mutawa A. (2011). Development of a suitable mine backfill material using mine waste for safe and economic ore production at Konkola mine (Zambia), M.Min.Sc Thesis, University of Zambia, School of Mines, Lusaka, 10-13.
- [4] Potvin Y. (1988). Empirical open stope design in Canada, PhD Thesis, Department of Mining and Mineral Processing, University of British Columbia, Canada.
- [5] Purwanto et al. (2013). Influence of stope design on stability of hanging wall decline in Cibaliung underground gold mine. International Journal of Geosciences, 4: 1-8.
- [6] Villaescusa E. (2003). Global extraction sequences in sublevel stopping. MPES 2003 Conference, Kalgoorlie, pp. 1-19.
- [7] Wang J, Milne D, Wegner L, Reeves M. (2007). Numerical analysis of the effects of stress and excavation surface geometry on the zone of relaxation around open stope hanging walls. International Journal of Rock Mechanics & Mining Sciences, 44(2): 289-298.