

REFERENCE

- [1] Kjarstad J, Johnsson F. (2008, Nov). Resources and future supply of oil. *Energy Policy* [online]. 37 (2), pp. 441–464. Available: <http://www.sciencedirect.com/science/article/pii/S0301421508005259>
- [2] Moser BR. (2009, Mar). Biodiesel production, properties, and feed-stocks. *In Vitro Cell Dev BioPlant* [online]. 45, pp. 229–266. Available: <http://link.springer.com/article/10.1007/s11627-009-9204-z>
- [3] Leung DYC, Wu X, Leung MKH. (2009, Nov). A review on biodiesel production using catalyzed transesterification. *Applied Energy* [online]. 87 (4), pp. 1083–1095. Available: <http://www.sciencedirect.com/science/article/pii/S0306261909004346>
- [4] Ziman Wang, Hongming Xu, et al. (2016, Feb). Experimental study on microscopic and macroscopic characteristics of diesel spray with split injectio. *Fuel* [online]. 174, pp. 140-152. Available: <http://www.sciencedirect.com/science/article/pii/S0016236116001046>
- [5] Balaji Mohan, Wenming Yang, et al. (2014, Nov). Experimental study of spray characteristics of biodiesel derived from waste cooking oil. *Energy* [online]. 88, pp. 622–632. Available: <http://www.sciencedirect.com/science/article/pii/S019689041400805X>
- [6] Raghu Palani1, Nallusamy Nallusamy, et al. (2015, Oct). Spray characteristics of diesel and derivatives in direct injection diesel engines with varying injection pressures. *Journal of Mechanical Science and Technology* [online]. 29 (10), pp. 4465–4471. Available: <http://link.springer.com/article/10.1007/s12206-0150945-9>
- [7] Xiang Wang, Zhiqiang Han. (2015, Nov). A numerical study of the effects of pressure fluctuations inside injection nozzle on high-pressure and evaporating diesel spray characteristics. *Applied Mathematical Modelling* [online]. 40, pp. 4032–4043. Available: <http://www.sciencedirect.com/science/article/pii/S0307904X15007283>
- [8] Youngsoo Park a, Joonsik Hwang, et al. (2015, Sep). Effects of diesel fuel temperature on fuel flow and spray characteristics. *Fuel* [online]. 162, pp. 1–7. Available: <http://www.sciencedirect.com/science/article/pii/S0016236115008984>
- [9] Donghoon Kim and Kihyun Kim. (2014, Jan). Comparison of Spray Structures of Diesel and Gasoline Using Modified Evaporation Model in Openfoam CFD Package. *SAE paper* [online]. 01-1417. Available: <http://papers.sae.org/2014-01-1417>
- [10] Bhupendra Singh Chauhan, Naveen Kumar, Haeng Muk Cho. (2011, Nov). A study on the performance and emission of a diesel engine fueled with Jatropa biodiesel oil and its blends. *Energy* [online]. 37 (1), pp. 616-622. Available: <http://www.sciencedirect.com/science/article/pii/S0360544211007109>
- [11] Hongzhan Xie, et al. (2015, Jun). An Experimental Study on the Macroscopic Spray Characteristics of Biodiesel and Diesel in a Constant Volume Chamber. *Energies* [online]. 8, pp. 5952-5972. Available: <http://web.b.ebscohost.com/ehost/detail/detail?sid=49c35386-30b2-45c6-8eb8aa2447431c7a%40sessionmgr105&vid=0&hid=102&bdata=JnNpdGU9ZWwhvc3QtbGl2ZQ%3d%3d>