

- Polymer Research, 1(1): 3-39. <https://doi.org/10.1016/j.aiepr.2018.05.001>
- [22] Werner, P., Altstädt, V., Jaskulka, R., Jacobs, O., Sandler, J.K., Shaffer, M.S., Windle, A.H. (2004). Tribological behaviour of carbon-nanofibre-reinforced poly (ether ether ketone). *Wear*, 257(9-10): 1006-1014. <https://doi.org/10.1016/j.wear.2004.07.010>
- [23] Gujar, S.S., Rukhande, S.W., Rathod, W.S. (2022). Sliding wear investigation of ni-based coating and SS 316L for hydraulic fracturing tools in water-diesel condition. *Journal of Failure Analysis and Prevention*, 22(2): 750-756. <https://doi.org/10.1007/s11668-022-01370-4>
- [24] Hussain, M.M., Gaval, V., Pratap, A., Rukhande, S. (2023). Tribological study of sunflower TMP ester and silica nanoparticles additives for hydrodynamic journal bearing application under boundary lubrication condition. *Industrial Lubrication and Tribology*, 75(2): 190-196. <https://doi.org/10.1108/ILT-08-2022-0251>
- [25] Rukhande, S.W., Rathod, W.S., Bhosale, D. (2022). High-temperature tribological investigation of APS and HVOF sprayed NiCrBSiFe coatings on SS 316L. *Tribology-Materials, Surfaces Interfaces*, 16(2): 98-109. <https://doi.org/10.1080/17515831.2021.1898887>
- [26] Vasconcelos, P.V.D.S.M. (2004). Fabrico rápido indirecto de ferramentas compósitas a partir de modelos de prototipagem rápida
- [27] Pourabas, B., Raeesi, V. (2005). Preparation of ABS/montmorillonite nanocomposite using a solvent/non-solvent method. *Polymer*, 46(15): 5533-5540. <https://doi.org/10.1016/j.polymer.2005.04.055>
- [28] Ryder, M.A., Lados, D.A., Iannacchione, G.S., Peterson, A.M. (2018). Fabrication and properties of novel polymer-metal composites using fused deposition modeling. *Composites Science and Technology*, 158: 43-50. <https://doi.org/10.1016/j.compscitech.2018.01.049>
- [29] Olivieri, F., Avolio, R., Gentile, G., Mazzone, A., Rizzi, R., Nacucchi, M., Lavorgna, M. (2023). High filler content acrylonitrile-butadiene-styrene composites containing tungsten and bismuth oxides for effective lead-free x-ray radiation shielding. *Polymer Composites*. <https://doi.org/10.1002/pc.27906>
- [30] Bankupalli, N., Rao, D.S., Krishna, T.V. (2021). Effect of process parameters and butadiene content on friction and wear behaviour of ABS components. *Materials Today: Proceedings*, 41: 416-421 <https://doi.org/10.1016/j.matpr.2020.09.808>
- [31] Garg, H.K., Singh, R. (2015). Comparison of wear behavior of ABS and Nylon6—Fe powder composite parts prepared with fused deposition modelling. *Journal of Central South University*, 22: 3705-3711. <https://doi.org/10.1007/s11771-015-2913-z>
- [32] Raj, S.S., Kuzmin, A.M., Subramanian, K., Sathiamoorthy, S., Kandasamy, K.T. (2021). Philosophy of selecting ASTM standards for mechanical characterization of polymers and polymer composites. *Materiale Plastice*, 58(3): 247-256 <https://doi.org/10.37358/Mat.Plast.1964>
- [33] Liu, L., Xu, H., Xiao, J., Wei, X., Zhang, G., Zhang, C. (2017). Effect of heat treatment on structure and property evolutions of atmospheric plasma sprayed NiCrBSi coatings. *Surface and Coatings Technology*, 325: 548-554. <https://doi.org/10.1016/j.surfcoat.2017.07.011>
- [34] Torgerson, T.B., Harris, M.D., Alidokht, S.A., Scharf, T.W., Aouadi, S.M., Chromik, R.R., Voevodin, A.A. (2018). Room and elevated temperature sliding wear behavior of cold sprayed Ni-WC composite coatings. *Surface and Coatings Technology*, 350: 136-145. <https://doi.org/10.1016/j.surfcoat.2018.05.090>
- [35] Dong, S., Song, B., Liao, H., Coddet, C. (2015). Deposition of NiCrBSi coatings by atmospheric plasma spraying and dry-ice blasting: Microstructure and wear resistance. *Surface and Coatings Technology*, 268: 36-45. <https://doi.org/10.1016/j.surfcoat.2014.09.025>
- [36] MP-320 Polymer Bearings. <http://technymon.com/mp-320.html>.

NOMENCLATURE

ABS	Acrylonitrile Butadiene Styrene
TiO ₂	Titanium Di Oxide
W	Tungsten
N	Newton
m	Metre
%	Percentage
COF	Co-efficient of Friction