

- factor of crosswind response of flexible structures with nonlinear aeroelastic effect. *Journal of Structural Engineering*, 140(12): 04014091. [https://doi.org/10.1061/\(asce\)st.1943-541x.0001017](https://doi.org/10.1061/(asce)st.1943-541x.0001017)
- [9] Shadmand, M.B., Balog, R.S., Abu-Rub, H. (2014). Model predictive control of PV sources in a smart DC distribution system: Maximum power point tracking and droop control. *IEEE Trans. Energy Convers.*, 29(4): 913-921. <https://doi.org/10.1109/tec.2014.2362934>
- [10] Shadmand, M., Balog, R.S., Abu Rub, H. (2014). Maximum power point tracking using model predictive control of a flyback converter for photovoltaic applications. *IEEE Power and Energy Conference at Illinois (PECI)*, pp. 1-5. <https://doi.org/10.1109/peci.2014.6804540>
- [11] Rebei, N., Benghanem, B., Hmidet, A., Hasnaoui, O. (2013). Study of photovoltaic water pumping system using scalar-DVC based control. *IEEE International Conference on Electrical Engineering and Software Applications (ICEESA)*, pp. 1-8. <https://doi.org/10.1109/iceesa.2013.6578461>
- [12] Bhavnesh, K., Yogesh, C.K., Shrivastava, V. (2013). Performance analysis of fuzzy based sensorless induction motor drive with photovoltaic source. *IEEE International Conference on Fuzzy Systems (FUZZ-IEEE)*, pp. 1-6. <https://doi.org/10.1109/fuzz-ieee.2013.6622460>