











- [1] Zhao H, Pang Z, Feng B. (2008). Research and Development of 500GJl-PwT Container--Generating Set. *I.C.E. & Power Plant* 25(5): 32-33. <https://doi.org/10.3969/j.issn.1673-6397.2008.05.008>
- [2] Li Y, Shu N, Han B. (2012). Study of optical cables selecting and laying in smart substation. *Water Resources and Power* 30(3): 167-169. <https://doi.org/10.3969/j.issn.1000-7709.2012.03.050>
- [3] Zhao R, Meng H. (2013). Design of the Container for 2800 kW Containerized Generator Set. *I.C.E. & Power Plant* 30(1): 11-18. <https://doi.org/10.3969/j.issn.1673-6397.2013.01.004>
- [4] Taghikhani M, Gholami A. (2009). Prediction of hottest spot temperature in power transformer windings with non-directed and directed oil-forced cooling. *International Journal of Electrical Power & Energy Systems* 31(7-8): 356-364. <https://doi.org/10.1016/j.ijepes.2009.03.009>
- [5] Taheri S, Vahedi A, Gholami A, Taheri H. (2008). Estimation of hot spot temperature in distribution transformer considering core design using FEM. *International Conference on Power and Energy 2008*. 1408-1413. <https://doi.org/10.1109/PECON.2008.4762699>
- [6] Chatzidimitriou A, Chrissomallidou N, Yannas S. (2006). Groud surface materials and microclimates in urban open spaces, 23rd Conference on Passive and Low Energy Architecture, Geneva, 1426-1434.
- [7] Doulos L, Santamouris M, Livada I. (2004). Passive cooling of outdoor urban spaces. *The Role of Materials Solar Energy* 77(2): 231-249.
- [8] Jang J, Chen C. (2015). Optimization of louvered-fin heat exchanger with variable louver angles. *Applied Thermal Engineering* 91:138-150. <https://doi.org/10.1016/j.applthermaleng.2015.08.009>
- [9] Gorman J, Carideo M, Sparrow E, Abraham J. (2015). Heat transfer and pressure drop comparison of louver- and plain-finned heat exchangers where one fluid passes through *flattened* tubes. *Case Studies in Thermal Engineering* 5(1): 122-126. <https://doi.org/10.1016/j.csite.2015.03.002>
- [10] Ching-Tsun H, Jiin-Yuh J. (2005). 3-D thermal-hydraulic analysis for louver fin heat exchangers with variable louver angle. *Applied Thermal Engineering* 26(14-15): 1629-1639. <https://doi.org/10.1016/j.applthermaleng.2005.11.019>
- [11] Yang L, Qi B, Chen J. (2015). Numerical simulation and analysis on louver arrangements of oblique needle louvered fin. *Mechanical Engineer* 47(12): 22-24. <https://doi.org/10.3969/j.issn.1002-2333.2015.12.009>
- [12] Kou L, Liao S, Liu Y. (2009). Numerical simulation for heat transfer performance of louvered fin. *Building Energy & Environment* 28(1): 6-9. <https://doi.org/10.3969/j.issn.1002-2333.2015.12.009>
- [13] Xie H, Chen K. (2010). Impact of point source height and window Configuration On Indoor air quality. *Journal of University of Shanghai for Science and Technology* 32(5): 413-417. <https://doi.org/10.3969/j.issn.1007-6735.2010.05.002>
- [14] Wan X, Su Y. (2004). Numerical simulation of effect of building structure on natural ventilation in industrial workshops with heat sources, Ph.D. dissertation, Department of Thermal Engineering, Donghua University, Shanghai, China