

- [14] Myers TG, Mitchell SL, Muchatibaya G, Myers MY. (2007). Acubic heat balance integral method for one dimensional melting of a finite thickness layer. *Int. J. Heat Mass Transfer* 50: 5305-5317.
- [15] Gupta RS. (1981). Dhirendra Kumar, Variable time step methods for one-dimensional Stefan problem with mixed boundary condition. *Int. J. Heat Mass Transfer* 24: 251-259.
- [16] Caldwell J, Chan CCh. (2000). Spherical solidification by the enthalpy method and the heat balance integral method. *Applied Mathematical Modelling* 24: 45-53.
- [17] Trp A. (2005). An Experimental and Numerical investigation of heat transfer during technical grade paraffin melting and solidification in a shell and tube latent thermal energy storage unit. *Int. J. of Solar Energy* 79: 648-660.
- [18] Thomas DG, Sajith BC, Gopi S. (2016). Performance analysis of a latent heat thermal energy storage system for solar energy applications. *International Conference on Emerging Trends in Engineering, Science and Technology* 24: 469-476.
- [19] Lamberg P, Lehtiniemi R, Anna-Maria H. (2004). Numerical and experimental investigation of melting and freezing processes in phase change material storage. *Int. J. of Thermal Sciences* 43: 277-287.
- [20] Savovic S, Caldwell J. (2009). Numerical solution of Stefan problem with time-dependent boundary conditions by variable space grid method. *Int. J. of Thermal Science* 13: 165-174.
- [21] Du YP, Ding YL. (2016). The value of thermal radiation in assessing the charge/discharge rate of high-grade thermal energy storage using encapsulated phase change materials (PCMs). *International Journal of Energy Research* 40(9): 1235-1244.
- [22] Mantelli H, Braga WF. (2011). Temperature profiles for diffusion problem precise solutions using heat balance integral method. *Journal of Thermophysics and Heat Transfer* 25(3): 443-449.
- [23] Srivastava M, Sinha MK. (2018). Computational analysis of encapsulated thermal energy phase change storage system. *International Journal of Mechanical Engineering and Technology* 9(5): 662-668.
- [24] Goodman TR. (1958). The heat balance integral and its application to problems involving a change of phase, *Trans. ASME Journal of Heat Transfer* 80: 335-342.
- [25] Garg R, Thakur H, Tripathi B. (2018). Numerical simulation of two-dimensional fluid flow problem using truly meshfree method. *Mathematical Modelling of Engineering Problems* 5(4): 357-364.

NOMENCLATURE

- C = Heat capacity
k = constant, k=1,2 for cylinder & sphere respectively
K = thermal conductivity, W/m K
L = latent heat, J/Kg
 Q_{τ} = non-dimensional total heat absorbed
R = radius, m
 r_i = inner radius, m
 S_t = Stefan number, $\frac{c(T_s - T_m)}{L}$
t = time, s
T = temperature, K
 T_o = melting temperature, K
 T_s = surface temperature, K

Greek symbols

- α = thermal diffusivity, m^2/s
 δ = Interface location
 η = non-dimensional radial distance of phase front, δ/r_i
 $\dot{\eta}$ = time rate of non-dimensional radial distance of phase front, $d\eta/d\tau$
 ξ = non-dimensional radial distance within phase change, r/r_i
 ρ = density, Kg/m^3
 θ = non-dimensional temperature, $\frac{T - T_m}{T_s - T_m}$
 τ = non-dimensional time, $\frac{\alpha t}{r_i^2}$