

REFERENCES

- [1] Bhattacharya B, Doloi BN, Sorkhel SK. (1999). Experimental investigation into electro-chemical discharges machining (ECDM) of non- conductive ceramic materials. *Journal of Material Processing Technology* 95: 145-154. [http://dx.doi.org/10.1016/S0924-0136\(99\)00318-0](http://dx.doi.org/10.1016/S0924-0136(99)00318-0)
- [2] Jain VK, Adhikary S. (2008). On the mechanism of material removal in electrochemical spark Machining of quartz under different polarity conditions. *Journal of Materials Processing Technology* 200: 460–470. <http://dx.doi.org/10.1016/j.jmatprotec.2007.08.071>
- [3] Raghuram V, Pramila T, Srinivasa YG, Narayanasamy K. (1995). Effect of the circuit parameter on the electrolytes in the electrochemical discharge phenomenon. *Journal of Materials Processing Technology* 52: 301–318. [http://dx.doi.org/10.1016/0924-0136\(94\)01615-8](http://dx.doi.org/10.1016/0924-0136(94)01615-8)
- [4] Kulkarni A., Sharan R, Lal GK. (2002). An experimental study of discharge mechanism in Electrochemical discharge machining. *International Journal of Machine Tools and Manufacture* 42: 1121–1127. [http://dx.doi.org/10.1016/S0890-6955\(02\)00058-5](http://dx.doi.org/10.1016/S0890-6955(02)00058-5)
- [5] McGeough AB, Khayry M, Munro W. (1983). Theoretical and experimental investigation of the Relative effects of spark erosion and electrochemical dissolution in electrochemical arc machining. *Annals of the CIRP* 31: 113–118. [https://doi.org/10.1016/S0007-8506\(07\)63373-3](https://doi.org/10.1016/S0007-8506(07)63373-3)
- [6] Yang CK. (2010). Effect of surface roughness of tool electrode materials in ECDM performance. *International Journal of Machine Tools & Manufacture* 50: 1088–1096. <https://doi.org/10.1016/j.ijmactools.2010.08.006>
- [7] Cao XD. (2009). Micro-structuring of glass with features less than 100µm by electrochemical discharge machining. *Precision Engineering* 33: 459–465. <https://doi.org/10.1016/j.precisioneng.2009.01.001>
- [8] Jana D. (2012). Micro-texturing channel surfaces on glass with spark assisted chemical engraving. *International Journal of Machine Tools & Manufacture* 57: 66–72. <https://doi.org/10.1016/j.ijmactools.2012.01.012>
- [9] Yang CK. (2011). Enhancement of ECDM efficiency and accuracy by spherical tool electrode. *International Journal of Machine Tools & Manufacture* 51: 528–535. <https://doi.org/10.1016/j.ijmactools.2011.03.001>
- [10] Basak I, Ghosh A. (1997). Mechanism of material removal in electrochemical discharge machining: a theoretical model and experimental verification. *Journal of Materials Processing Technology* 71: 350–359. [https://doi.org/10.1016/S0924-0136\(97\)00097-6](https://doi.org/10.1016/S0924-0136(97)00097-6)
- [11] Coteață M. (2008). Electrochemical discharge machining of small diameter holes. *International Journal of Material Forming* 1: 1327-1330. <https://doi.org/10.1007/s12289-008-0148-3>
- [12] Indrajit S, Mukherjee S, Biswas K. (2017). A review of energy harvesting technology and its potential applications. *Environmental and Earth Sciences Research Journal* 4(2): 33-38. <https://doi.org/10.18280/eesrj.040202>

NOMENCLATURE

DC	Direct current
NaOH	Sodium hydroxide
KOH	Potassium Hydroxide
S/N ratio	Signal to noise ratio
TWR	tool wear rate
MRR	material removal rate
EC	Electrolyte Concentration